elumen8 CABLE DATASHEET

SPECIFICATION	
Description :	TOUR 4 Core 4 x 2.5mm2 Speaker Cable SP4X2.5B
Туре:	Speaker cable
Versions:	CABL611 - Black, 100m length CABL611B - Black, 300m length Also available by the metre

CONSTRUCTION



Touring quality, 4 core loudspeaker cable for medium power rental applications. The cable is constructed from four multi-strand, oxygen-free cores within a super flexible PVC outer jacket. The loudspeaker cable can be coiled and re-coiled multiple times whilst retaining its flexibility and shape. Each internal core is made up from seven cores, each one featuring 45 strands of oxygen-free high grade copper.

Conductor:	Material - Bare Copper (OFC) Construction - 7 x 45 x 0.10mm Cross section - 2.5mm² x 4
Insulation:	Material - Polyvinylchloride (PVC) Thickness - 0.5mm Diameter - 3.5mm x 4 core Colour - 1) White, 2) Red, 3) Black, 4) Yellow
Filler:	Material - Cotton + Paper
Outer jacket:	Material - Polyvinylchloride (PVC) Thickness - 1.2mm Diameter - 11.0mm

OPERATION TEMP.

ELECTRICAL CHARACTERISTIC

-15°C ~ 60°C

 $\label{eq:conductor} \textbf{Conductor resistance:} \quad 7.8 \Omega/km$