

ECO SLIMLINE FLOODLIGHT

Technical Data Sheet

Created on: 16-12-2019



© Luceco plc

Address:

Luceco plc,
Caparo House,
103 Baker Street,
London, W1U 6LN.

Telephone:

+44 (0)1952 238 100

Email Address:

info@luceco.com

ECO Slimline Floodlight

- Die-cast aluminium floodlight with fixing bracket
- Light output equivalent to halogen supplied with 0.75M cable
- noname3

Overview

Code	Colour Temperature	Lumens	Wattage	Equivalent
EFLD10B40	4000	800	10	100W HLG
EFLD10W40	4000	800	10	100W HLG
EFLD20B40	4000	1600	20	200W HLG
EFLD20W40	4000	1600	20	200W HLG
EFLD30B40	4000	2400	30	300W HLG
EFLD30W40	4000	2400	30	300W HLG
EFLD50B40	4000	4000	50	500W HLG
EFLD50W40	4000	4000	50	500W HLG

Construction & Installation

	Length (mm)	Width (mm)	Height (mm)	Fixing Centre L (mm)	Fixing Centre W (mm)	Weight(kg)	Ingress Protection	Impact Resistance
EFLD10B40	144	50	125	TBC	TBC	0.4	IP65	IK06
EFLD10W40	144	50	125	TBC	TBC	0.4	IP65	IK06
EFLD20B40	141	50	150	TBC	TBC	0.5	IP65	IK06
EFLD20W40	141	50	150	TBC	TBC	0.5	IP65	IK06
EFLD30B40	176	50	185	TBC	TBC	0.7	IP65	IK06

EFLD30W40	176	50	185	TBC	TBC	0.7	IP65	IK06
EFLD50B40	205	50	211	TBC	TBC	1.1	IP65	IK06
EFLD50W40	205	50	211	TBC	TBC	1.1	IP65	IK06

Technical Information

	Life time hours	Temperature range	In-Rush Current (A,uS)	Earth Leakage mA	Voltage Range	Frequency(hz)	Approval	Electrical Class	Power Factor
EFLD10B40	25000	20°C 25°C	TBC	TBC	220V-240V	50	CE	1	0.5
EFLD10W40	25000	20°C 25°C	TBC	TBC	220V-240V	50	CE	1	0.5
EFLD20B40	25000	20°C 25°C	TBC	TBC	220V-240V	50	CE	1	0.5
EFLD20W40	25000	20°C 25°C	TBC	TBC	220V-240V	50	CE	1	0.5
EFLD30B40	25000	20°C 25°C	TBC	TBC	220V-240V	50	CE	1	0.9
EFLD30W40	25000	20°C 25°C	TBC	TBC	220V-240V	50	CE	1	0.9
EFLD50B40	25000	20°C 25°C	TBC	TBC	220V-240V	50	CE	1	0.9
EFLD50W40	25000	20°C 25°C	TBC	TBC	220V-240V	50	CE	1	0.9

ECO Slimline Floodlight PIR

- Die-cast aluminium floodlight with fixing bracket
- Light output equivalent to halogen supplied with 0.75M cable
- noname3

Overview

Code	Colour Temperature	Lumens	Wattage	Equivalent
EFLD10B40P	4000	800	10	100W HLG
EFLD10W40P	4000	800	10	100W HLG
EFLD20B40P	4000	1600	20	200W HLG
EFLD20W40P	4000	1600	20	200W HLG
EFLD30B40P	4000	2400	30	300W HLG
EFLD30W40P	4000	2400	30	300W HLG
EFLD50B40P	4000	4000	50	500W HLG
EFLD50W40P	4000	4000	50	500W HLG

Construction & Installation

	Length (mm)	Width (mm)	Height (mm)	Fixing Centre L (mm)	Fixing Centre W (mm)	Weight(kg)	Ingress Protection	Impact Resistance
EFLD10B40P	181	70	125	TBC	TBC	0.4	IP54	IK06
EFLD10W40P	181	70	125	TBC	TBC	0.4	IP54	IK06
EFLD20B40P	192	70	150	TBC	TBC	0.5	IP54	IK06
EFLD20W40P	192	70	150	TBC	TBC	0.5	IP54	IK06
EFLD30B40P	225	70	186	TBC	TBC	0.8	IP54	IK06

EFLD30W40P	225	70	186	TBC	TBC	0.8	IP54	IK06
EFLD50B40P	251	70	211	TBC	TBC	1.2	IP54	IK06
EFLD50W40P	251	70	211	TBC	TBC	1.2	IP54	IK06

Technical Information

	Life time hours	Temperature range	In-Rush Current (A,uS)	Earth Leakage mA	Voltage Range	Frequency(hz)	Approval	Electrical Class	Power Factor
EFLD10B40P	25000	20°C 25°C	TBC	TBC	220V-240V	50	CE	1	0.5
EFLD10W40P	25000	20°C 25°C	TBC	TBC	220V-240V	50	CE	1	0.5
EFLD20B40P	25000	20°C 25°C	TBC	TBC	220V-240V	50	CE	1	0.5
EFLD20W40P	25000	20°C 25°C	TBC	TBC	220V-240V	50	CE	1	0.5
EFLD30B40P	25000	20°C 25°C	TBC	TBC	220V-240V	50	CE	1	0.9
EFLD30W40P	25000	20°C 25°C	TBC	TBC	220V-240V	50	CE	1	0.9
EFLD50B40P	25000	20°C 25°C	TBC	TBC	220V-240V	50	CE	1	0.9
EFLD50W40P	25000	20°C 25°C	TBC	TBC	220V-240V	50	CE	1	0.9