



HSC15 HIGH-PERFORMANCE CONFERENCE HEADSET



HIGH LEVEL CONFERENCE SPEECH

The HSC15 high level conference headset is AKG's latest on-ear headset in the field of conferencing. Sophisticated design pairs with high quality audio and advanced security technology. Optimal adjustment to any head size and lightweight design allow hours of use, while forgetting the presence of the headset. After the conference wiping with a simple hygienic tissue will prepare the unit for the next user, without the need to exchange expensive foam cushions. The steel bow is made of stainless spring steel to keep it's shape for the entire lifetime while it is also flexible enough to achieve different wearing positions. The microphone is built on a slim line omnidirectional condenser capsule, reproducing excellent sound quality, even when the microphone is not positioned perfectly.

The HSC15 is the ideal tool for the work of professional interpreters. It features two pieces of 3,5mm jack connectors, which are common in most interpreter desks and also allow the use with a PC/laptop. The cable is very soft and TPU covered in order to reduce the structure-borne noise.

HIGHLIGHTS

- » Wide frequency range for modern multimedia conferences
- » On-ear, ultra lightweight design and wide adjustment range for maximum wearing comfort
- » Rugged construction for an extra-long life of reliability and stability
- » Low impedance technology for lots of SPL to override room noise when needed
- » Cleanable high gloss polished plastic ear cups comply with all hygienic standards



- » The headband is made of a soft TPE material to guarantee comfortably wearing properties
- » Slim line gooseneck for optimal positioning of the microphone
- » Omni directional condenser element reproduces linear sound quality for optimal intelligibility

APPLICATIONS

When users are changing and/or long using time is required, such as:

- » Conferencing
- » VOIP
- » Assistive listening
- » Schools

KEY SPECIFICATIONS

Contact pressure ear pads to av. head Weight without cable Weight with cable Cable diameter Cable length Plug Dimensions	2,2N 108g 118g ø2, 5 mm 1500 mm 2x ø3, 5 mm stereo gold plated 199 x 156mm
Item number	3446H00010
Earphone Diameter of ear caps Ear adjustment via gimbal joint Head adjustment range for head size Acoustics Impedance Sensitivity THD Frequency range	ø53mm ±10° in each direction 63mm / side 40mm speaker 32 ohms 113 +/-3 dB spl/ mW (@32ohms) <1% @1kHz@1mW 20Hz-20.000 Hz
<u>Micboom</u> Directivity Electrical impedance mic Sensitivity Frequency range Equivalent noise level Recommended load impedance	Omi directional < 1 KOhm 8.5mV/Pa (powered with 5V & 4k7 ohms) 20Hz-20.000 Hz 32 dB(A) > 2 KOhm



AKG ACOUSTICS GMBH LAXENBURGER STRASSE 254, 1230 VIENNA/AUSTRIA AKG ACOUSTICS, U.S. 8400 BALBOA BOULEVARD, NORTHRIDGE, CA 91329, U.S.A.

© 2015 HARMAN International Industries, Incorporated. All rights reserved. AKG is a trademark of AKG Acoustics GmbH, registered in the United States and/or other countries.

Features, specifications and appearance are subject to change without notice.