


6MD38



LF Drivers - 6.5 Inches







- 240 W continuous program power capacity
 38 mm (1.5 in) aluminium voice coil
 130 6000 Hz response

- 96 dB sensitivity







SPECIFICATIONS

170 mm (6.5 in)
8 Ω
6.5 Ω
120 W
240 W
96.0 dB
130 - 6000 Hz
38 mm (1.5 in)
Aluminium
Glass Fibre
9.0 mm (0.35 in)
6.0 mm (0.25 in)
1.4 T

DESIGN

Surround Shape	Triple Roll
Cone Shape	Exponential
Magnet Material	Ferrite
Spider	Single
Pole Design	T-Pole
Woofer Cone Treatment	None

PARAMETERS⁴

Resonance Frequency	130 Hz
Re	5.7 Ω
Qes	0.49
Qms	3.7
Qts	0.44
Vas	3.0 dm ³ (0.1 ft ³)
Sd	132.0 cm ² (20.5 in ²)
η٥	1.4 %
Xmax	± 2.0 mm
Xvar	± 4.5 mm
Mms	12.0 g
BI	10.5 Txm
Le	0.25 mH
EBP	265 Hz

MOUNTING AND SHIPPING INFO

Overall Diameter	187 mm (7.4 in)
Bolt Circle Diameter	172 mm (6.7 in)
Baffle Cutout Diameter	145.0 mm (5.7 in)
Depth	82 mm (3.2 in)
Flange and Gasket Thickness	₅ 9 mm (0.35 in)
Air Volume Occupied by Drive	or
Air volume occupied by Drive	0.8 dm ³ (0.03 ft ³)
Net Weight	2.2 kg (4.8 lb)
Shipping Units	1
Shipping Weight	2.4 kg (5.29 lb)
Shipping Box 210x210x125 mm (8.27x8.27x4.92 in)

SERVICE KIT

Recone kit	RCK06MD388

2 hours test made with continuous pink noise signal within the range Fs-10Fs. Power calculated on rated minumum impedance. Loudspeaker in free air.
 2. Power on Continuous Program is defined as 3 dB greater than the Nominal rating.
 3. Applied RMS Voltage is set to 2.83 V for 8 ohms Nominal Impedance.
 4. Thiele-Small parameters are measured after a high level 20 Hz sine wave preconditioning test.