

STRIKE Array 2C

FEATURES

- Intense 2 pod color blinder/strobe rated IP65 for all-weather use
- Full range of color and excellent rendition of any color temperature of white
- Emulated "red shift" to mimic incandescent fixtures perfectly.
- Individual pan (or tilt depending on mount orientation) of each head to allow for directional adjustment of light output.
- Innovative interlocking system to connect multiple STRIKE Array family fixtures together.
- Multiple mounting locations and repositionable yoke with ¼ turn adaptors for creative and convenient rigging options
- Independent pod control and strobe functionality for high-impact effects on the fly



SPECIFICATIONS

OPTICAL

- Light Source: 134 LEDs (56 quad-color RGBA, 78 WW) 2.7 to 4.32 W, (871 mA), 50,000 hours life expectancy.
- Color Temperature (range): 2800 to 6500 K
- Color Temperature (at full): 6528 K
- CRI: 94.4
- CRI (@3200K): 94.4
- Beam Angle: 59.1°
- Field Angle: 102.1°
- Lumens: 25,917
- Illuminance (total): 979 lux @ 5 m
- Selectable PWM: 600 Hz, 1200 Hz, 2000 Hz, 4000 Hz, 6000 Hz, 25,000 Hz

DYNAMIC EFFECTS

- Dimmer: Electronic
- Shutter/Strobe: Electronic
- Strobe Rate: 0 to 30 Hz
- Standalone Color Mixing: Yes
- Color Temperature Presets: Yes
- Dim Modes: 4
- Dim Curves: 4
- Built-in Automated Programs: Yes

CONSTRUCTION / PHYSICAL

- Dimensions: 19.13 x 7.45 x 10.37 in (486 x 189.3 x 263.5 mm)
- Weight: 20.6 lb (9.4 kg)
- Exterior Color: Black
- Housing Material: Aluminum alloy

CONNECTIONS

- Power Connection: Edison (Local) plug to Seetronic Powerkon IP65
- Power Input: Seetronic Powerkon IP65
- Power Output: Seetronic Powerkon IP65

- Data Connectors: 5-pin Seetronic IP65 XLR or Seetronic IP65 etherCON
- Cable Length (power): 5 ft (1.5 m)
- Software Update: USB-C

CONTROL

- Control Protocol: Art-Net, sACN, DMX, RDM
- Modes/Personalities: 10 personalities (1ch, 3ch, 5ch, 7ch, 10ch, 12ch1, 12ch2 13ch, 16ch, HSV)

ELECTRICAL

- Input Voltage: 100 to 240 VAC, 50/60 Hz (auto-ranging)
- Power Linking: 2 units @ 120 V; 4 units @ 208 V; 4 units @ 230 V
- Power and Current: 600 W, 5.000 A @ 120 V, 60 Hz
- Power and Current: 583 W, 2.780 A @ 208 V, 60 Hz
- Power and Current: 581 W, 2.491 A @ 230 V, 50 Hz

CERTIFICATIONS / QUALIFICATIONS

- CE, MET, FCC, ETL, cULus
- IP Rating: IP65, outdoor/wet, with pressure equalizing M12 GORE valve
- Temperature (Ambient): -4 °F to 113 °F (-20 °C to 45 °C)

WHAT'S INCLUDED

- STRIKE Array 2C
- Seetronic Powerkon IP65
- Omega bracket with mounting hardware

OPTIONAL ACCESSORIES

- STRIKE Array Flush Bracket
- Professional Clamps: CTC-50HC, CTC-50HCN
- Safety Cable: SC-08
- IP Rated Seetronic® Powerkon Extensions
- IP Rated DMX cables
- IP Rated EtherCon Cables
- UPLOAD 03 software uploader