

# Freedom Par Q12

- 100% TRUE wireless, battery-operated, quad-color (RGBA) LED uplight with built-in D-Fi transceiver
- New secondary optics provide perfect color blending with nearly no artifacts
- Magnetic diffuser pops on or off with ease and widens the coverage area
- OLED display allows for full-text and to easily change fixture settings
- Built-in RF receiver for wireless control using the RFC or RFC-XL optional remotes
- Adjust the projection angle using the spring-loaded kickstand
- Extend the fixture's lifespan with the onboard charge and discharge protection circuitry
- Achieve smooth LED fading with built-in dimming curves
- Compact and lightweight design easily fits inside sticks of TRUSST®



## Specifications

- DMX Channels: 4, 6, or 14
- DMX Connectors: 3-pin XLR
- Light Source: 12 LEDs (quad-color RGBA) 6W, (1.5 A), 50,000 hours life expectancy
- Strobe Rate: 0 to 20 Hz
- Beam Angle: 12°
- Field Angle: 23°
- Beam Angle (with diffuser): 25°
- Field Angle (with diffuser): 49°
- Illuminance: 4,185 lux @ 2 m
- Illuminance (with diffuser): 1,005 lux @ 2 m
- Lumens: 1,255
- Maximum Run Time (all on): up to 7 hours
- Maximum Run Time (single color): up to 9.5 hours
- Recharge Time: 4 hours
- Operating Frequency: 2.412 to 2.484 GHz
- Max Unobstructed Distance: 600 ft (183 m)
- Startup Temperature: -4 °F to 113 °F (-20 °C to 45 °C)
- Operating Temperature: -22 °F to 113 °F (-30 °C to 45 °C)
- Input Voltage: 24 VDC, 1.5 A (external power supply: 24 VDC, 50/60 Hz)
- Power and Current: 22 W, 0.3 A @ 120 V, 60 Hz
- Power and Current: 22 W, 0.2 A @ 230 V, 50 Hz
- Weight: 5.4 lbs (2.4 kg)
- Size: 8.7 x 7.8 x 4.8 in (222 x 197 x 123 mm)
- Optional Controllers: RFC, RFC-XL
- Approvals: CE, RoHS, FCC

\*White sleeve is sold separately

