

# GigBAR Bridge Beam ILS

- 3-in-1 lighting system that includes moving heads, RGBW rings and washes pre-mounted on a single bar
- Quickly and securely connect multiple fixtures with the built-in locking system
- Built-in DFI transceiver communicates DMX or ILS signals wirelessly
- ILS compatibility for use in the ILS ecosystem
- Safely mounts onto truss or mobile tripods using the removable bracket
- Easy navigation and access all functions directly from the full-color LCD display
- Totem Mode keeps the moving heads focused on the dance floor
- Save time running cables and extension cords by power linking multiple units
- Use the included RF remote to trigger the built-in shows without needing line of sight



## Specifications

- DMX Channels: 3, 24 or 60
- DMX Connectors: 3-pin XLR
- Pan and Tilt: 540°/270°
- Pan and Tilt Ranges: 180° 360° 540° Pan / 90° 180° 270° tilt
- Light Source (moving heads): 2 LEDs (RGBW) 80 W total (2.8 A), 50,000 hours life expectancy
- Light Source (wash): 4 LEDs (RGBAW+UV) 40 W total (2.6 A), 50,000 hours life expectancy
- Light Source (LED ring): 48 LEDs (RGBW) 10 W total 50,000 hours life expectancy
- Strobe Rate: 0 to 20 Hz
- PWM Frequency: 1200 Hz
- Beam Angle (moving head): 5°
- Beam Angle (wash): 20°
- Field Angle (wash): 37°
- Operating Frequency: 2.4 GHz
- Illuminance (moving head) : 24,670 @ 2 m (per head)
- Illuminance (wash) : 525 Lux @ 2 m (per section)
- Max Unobstructed Distance (D-Fi): 600 ft (183 m)
- Power Linking: 9 units @120 V; 18 units @ 230 V
- Input Voltage: 100 to 240 VAC, 50/60 Hz (auto-ranging)
- Power and Current: 147 W, 1.2 A 120 V, 60 Hz
- Power and Current: 144 W, 0.6 A 230 V, 50 Hz
- Fits Tripod Sizes: 1.5 in (37.4 mm)
- Approvals: CE, RoHS, FCC

- Weight: 16.4 lbs (7.5 kg)
- Size: 25 x 2.6 x 11.4 in (635 x 65 x 290 mm)
- Optional Controllers: RFC, RFC-XL, ILS Command

