

# Shocker Panel FX IP

- Outdoor-rated versatile blinder, wash and strobe light, with compelling eye candy effects
- Neutrik TRUE1 power input/output connections save setup time while maintaining water resistance
- 16 controllable sections (8 RGB + 8 white) provide creative programming flexibility
- Robust housing repels the elements in outdoor situations
- Password-protected and touch-sensitive digital display
- Trigger eye-catching, built-in macros via the display or DMX
- Integrated GORE valve allows the fixture to breathe and prevents internal humidity build-up
- Easily transported in the optional CHS-25 VIP gear bag



## Specifications

- DMX Channels: 8, 18, 34 or 47
- DMX Connectors: 3-pin XLR
- Light Source: 480 LEDs (tri-color) 2W, (1A), 50,000 hours life expectancy
- Light Source: 32 LEDs (cool white) 1.8 W (0.5 A), 50,000 hours life expectancy
- Strobe Rate: 0 to 20 Hz
- Beam Angle: 119°
- Field Angle: 158°
- Illuminance : 1,131 lux @ 2 m
- Lumens: 13,626
- IP Rating: IP66
- Startup Temperature: -4 °F to 113 °F (-20 °C to 45 °C)
- Operating Temperature: -22 °F to 113 °F (-30 °C to 45 °C)
- Cable Length: 5 ft (1.5 m)
- Power and Current: 238 W, 2 A @ 120 V, 60 Hz
- Power and Current: 231 W, 1 A @ 230 V, 50 Hz
- Power Linking: 6 units @ 120 V; 11 units @ 230 V
- Input Voltage: 100 to 240 VAC, 50/60 Hz (auto-ranging)
- Weight: 10.4 lbs (4.7 kg)
- Size: 12.9 x 5.1 x 6.8 in (330 x 130 x 173 mm)
- Approvals: CE, ROHS, MET