

Amhaze Stadium 2X IP

FEATURES

- Compact, professional hazer gives high quality haze for live lighting applications
- Suitable for temporary outdoor/wet use
- Continuous operation produces haze for medium to large applications
- Our innovative, fully serviceable heater assembly is designed for maximum efficiency and longevity. Enjoy easy internal servicing and cleaning, ensuring optimal performance with minimal downtime. Plus, the replaceable heater core extends the product's lifespan while reducing waste—delivering cost savings and sustainability without compromising on reliability.
- Our innovative heater design significantly reduces clogging, ensuring smooth operation, minimal maintenance, and enhanced reliability for long-term performance
- Adjustable vent louver for directional haze flow
- Ships in integrated, rugged flight case, suitable for rental/touring applications with removeable front cover with storage for accessories
- Designed for seamless compatibility, this unit utilizes Chauvet's standard 140D Omega Mounting Brackets, allowing for easy integration with standard mounting hardware for quick and secure installation.
- Experience precise control with continuous variable haze output and adjustable blower speed, easily fine-tuned via DMX integration or intuitive manual knobs for seamless customization.



SPECIFICATIONS

DYNAMIC EFFECTS

- Fan Performance: 164 cfm
- Low Fluid Shutdown: Yes

CONSTRUCTION / PHYSICAL

- Dimensions: 26 x 16 x 6.75 in (660 x 406 x 171.45 mm)
- Weight: 48.8 lb (22.13 kg)
- Exterior Color: Black
- Housing Material: Aluminum alloy, Aluminum diecast, High-impact flame-retardant polymer, Steel
- Tank Capacity: 1.32 gal (5 l)
- Fluid Consumption: 9.5 ml/min
- Maximum Runtime: 8 hrs

CONNECTIONS

- Power Connection: Edison (Local) plug to Seetronic Powerkon (powerCON Compatible)
- Power Input: Seetronic Powerkon IP65
- Data Connectors: 5-pin IP65 XLR
- Cable Length (power): 5 ft (1.5 m)
- Firmware upgrades: USB type-C

CONTROL

- Control Protocol: DMX, RDM
- DMX Channels: 2
- Modes/Personalities: 1 personality (2ch)
- On-Board Control: Yes

ELECTRICAL

- Input Voltage: 120 VAC, 60 Hz or 230 VAC, 50 Hz
- Power and Current: 511 W, 4.26 A @ 120 V, 60 Hz
- Power and Current: 722 W, 3.14 A @ 230 V, 50 Hz [1.2 A inrush]
- Heat-up Time: 6 min
- Fuse (120V model): F8 A, 250 V
- Fuse (230V model): F5 A, 250 V

CERTIFICATIONS / QUALIFICATIONS

- CE, UKCA
- IP Rating: IP65, temporary outdoor/wet use
- Temperature (Ambient): -4 °F to 113 °F (-20 °C to 45 °C)

WHAT'S INCLUDED

- Amhaze Stadium II IP
- Seetronic IP 65 Powerkon power cord
- 2x Mounting brackets
- Output nozzle assembly
- Front Cover

OPTIONAL ACCESSORIES

- Neutrik powerKON cables
- DMX Cables