

Rogue Outcast 3X Wash

FEATURES

- Fully-featured IP65 RGBW LED yoke wash fixture with LED zone control, zoom, durable, and lightweight aluminum/magnesium alloy body.
- 16-bit dimming of master dimmer, as well as individual colors for smooth control of fades
- 37 RGBW LEDs, 25 W each
- 5-pin DMX input/output connections
- 9 zones of LED control for pixel mapping control
- Fast/ smooth pan and tilt movement
- RDM-enabled for remote addressing and trouble shooting
- Selectable PWM options for camera operation
- Easy-to-read OLED display with simple, effective menu options
- User-selectable calibrated white for 7500 K at full output
- 6 distinct dimming modes for advanced control
- Easy-to-read OLED display with simple and effective menu options
- Simple and complex DMX channel profiles for programming versatility
- USB-C port for uploading software



SPECIFICATIONS

OPTICAL

- Light Source: 37 LEDs (quad-color RGBW) 25 W, (1.5 A), 50,000 hours life expectancy
- Color Temperature (range): 2800 to 10000 K
- Beam Angle: 9.3° to 33.9°
- Field Angle: 11.6° to 49.5°
- Cutoff angle: 13.1° to 62.6°
- Zoom Angle: 9.3° to 62.6°
- Lumens – Source: 17,000
- Lumens – Output: 13,440
- Illuminance (9.3°) : 18,260 lux @ 5 m
- Illuminance (62.6°):1,556 lux @ 5 m
- Selectable PWM: 600 Hz, 1,200 Hz, 2,000 Hz, 4,000 Hz, 6,000 Hz, 15,000 Hz

DYNAMIC EFFECTS

- Pan and Tilt: 540°/270°
- Pan and Tilt Ranges: 180°, 360°, 540° Pan/90°, 180°, 230° Tilt.
- Dimmer: Electronic
- Shutter/Strobe: Electronic
- Zoom: Motorized
- Strobe Rate: 0 to 25 Hz
- Standalone Color Mixing: Yes
- Color Temperature Presets: Yes
- Dim Curves: 4
- Built-in Automated Programs: Yes
- Customizable Programs: No

- Recall Custom Programs: No

CONSTRUCTION / PHYSICAL

- Dimensions: 15.59 x 11.73 x 17.20 in (396 x 298 x 437 mm)
- Dimensions (shipping size): 23.62x 14.17 x 18.70 in (600 x 360 x 475)
- Weight: 38.2 lb. (17.38kg)
- Exterior Color: Black
- Housing Material: High-impact flame-retardant polymer.

CONNECTIONS

- Power Connection: Edison (local) plug to Seetronic PowerKON IP65
- Power Input: Seetronic PowerKON IP65
- Power Output: Seetronic PowerKON IP65
- Data Connectors: 5-pin XLR
- Cable Length (power): 5 ft (1.5 m)

CONTROL

- Control Protocol: DMX, RDM
- DMX Channels: 21, 62, 71, 107
- Modes/Personalities: 4 personalities

ELECTRICAL

- Input Voltage: 100 to 240 VAC, 50/60 Hz (auto-ranging)
- Power Linking: 2 units @ 120 V; 3 units @ 208 V; 3 units @ 230 V
- Power and Current: 711 W, 5.98 A @ 120 V, 60 Hz
- Power and Current: 701 W, 3.40 A @ 208 V, 60 Hz
- Power and Current: 695 W, 3.07 A @ 230 V, 50 Hz

CERTIFICATIONS / QUALIFICATIONS

- CE, MET, FCC, FCC, UKCA
- IP Rating: IP65, temporary outdoor/wet use
- Temperature (Ambient): -4 °F to 113 °F (-20 °C to 45 °C)

WHAT'S INCLUDED

- Rogue Outcast 3X Wash
- Seetronic PowerKon IP65 power cord
- (2) 140D Omega brackets with mounting hardware

OPTIONAL ACCESSORIES

- Professional Clamps: CTC-50HC, CTC-50HCN
- Safety Cable: SC-08
- Seetronic IP65 PowerKon cables
- DMX Cables
- UPLOAD 08 software uploader