

WELL POD 2 – 15° Filter Pack

FEATURES

- Easily install and widen the beam angle of the WELL POD 2 from 11.5° to 18.9°
- Small size makes storage in charging case simple
- Simple installation and removal for on site application
- Easily identifiable single notch for beam angle identification
- Ships in packs of 6

SPECIFICATIONS

OPTICAL

- Beam Angle: 18.9°
- Field Angle: 37.3°
- Illuminance: 311 lux @ 5 m (AC)
- Lumens: 1254 (AC)
- Illuminance: 125 lux @ 5 m (Battery curve off)
- Lumens: 503 (Battery curve off)
- Illuminance: 145 lux @ 5 m (5 hr)
- Lumens: 588 (5 hr)
- Illuminance: 91 lux @ 5 m (8 hr)
- Lumens: 372 (8 hr)
- Illuminance: 58 lux @ 5 m (12 hr)
- Lumens: 235 (12 hr)
- Illuminance: 37 lux @ 5 m (18 hr)
- Lumens: 150 (18 hr)

CONSTRUCTION / PHYSICAL

- Dimensions: 4.33 in dia. (110 mm dia)
- Weight: 0.05 lb (0.025kg)

CERTIFICATIONS / QUALIFICATIONS

- CE
- IP Rating: IP65, temporary outdoor/wet use

WHAT'S INCLUDED

- WELL POD 2 15° Filter X 6

