

WELL POD 2 60° x 10° Filter Pack

FEATURES

- Easily install and widen the beam angle of the WELL POD 2 from 11.5° to 16.3 x 46.1°
- Small size makes storage in charging case simple
- Simple installation and removal for on site application
- Easily identifiable double notch for beam angle identification
- Ships in packs of 6

SPECIFICATIONS

OPTICAL

- Beam Angle: 16.3 X 46.1°
- Illuminance: 161 lux @ 5 m (AC)
- Lumens: 1400 (AC)
- Illuminance: 66 lux @ 5 m (Battery curve off)
- Lumens: 573 (Battery curve off)
- Illuminance: 77 lux @ 5 m (5 hr)
- Lumens: 666 (5 hr)
- Illuminance: 48 lux @ 5 m (8 hr)
- Lumens: 421 (8 hr)
- Illuminance: 31 lux @ 5 m (12 hr)
- Lumens: 268 (12 hr)
- Illuminance: 20 lux @ 5 m (18 hr)
- Lumens: 170 (18 hr)

CONSTRUCTION / PHYSICAL

- Dimensions: 4.33 in dia. (110 mm dia)
- Weight: 0.05 lb (0.025kg)

CERTIFICATIONS / QUALIFICATIONS

- CE
- IP Rating: IP65, temporary outdoor/wet use

WHAT'S INCLUDED

- WELL POD 2 60x10° Filter X 6

