

WELL POD 3 15° Filter Pack

FEATURES

- Easily install and widen the beam angle of the WELL POD 3 from 12.1° to 19.7°
- Small size makes storage in charging case simple
- Simple installation and removal for on site application
- Easily identifiable single notch for beam angle identification
- Ships in packs of 4

SPECIFICATIONS

OPTICAL

- Beam Angle: 19.7°
- Field Angle: 40.3°
- Illuminance: 626 lux @ 5 m (AC)
- Lumens: 2841 (AC)
- Illuminance: 369 lux @ 5 m (Battery curve off)
- Lumens: 1680 (Battery curve off)
- Illuminance: 385 lux @ 5 m (5 hr)
- Lumens: 1751 (5 hr)
- Illuminance: 242 lux @ 5 m (8 hr)
- Lumens: 1107 (8 hr)
- Illuminance: 146 lux @ 5 m (12 hr)
- Lumens: 669 (12 hr)
- Illuminance: 96 lux @ 5 m (18 hr)
- Lumens: 438 (18 hr)

CONSTRUCTION / PHYSICAL

- Dimensions: 5.82 in dia. (148 mm dia)
- Weight: 0.07 lb (0.031kg)

CERTIFICATIONS / QUALIFICATIONS

- CE
- IP Rating: IP65, temporary outdoor/wet use

WHAT'S INCLUDED

- WELL POD 3 15° Filter X 4

