

WELL POD 3 60X10° Filter Pack

FEATURES

- Easily install and widen the beam angle of the WELL POD 3 from 12.1° to 17.9 x 41.7°
- Small size makes storage in charging case simple
- Simple installation and removal for on site application
- Easily identifiable double notch for beam angle identification
- Ships in packs of 4

SPECIFICATIONS

OPTICAL

- Beam Angle: 17.9 X 41.7°
- Illuminance: 288 lux @ 5 m (AC)
- Lumens: 2683 (AC)
- Illuminance: 162 lux @ 5 m (Battery curve off)
- Lumens: 1515 (Battery curve off)
- Illuminance: 176 lux @ 5 m (5 hr)
- Lumens: 1646 (5 hr)
- Illuminance: 112 lux @ 5 m (8 hr)
- Lumens: 1044 (8 hr)
- Illuminance: 68 lux @ 5 m (12 hr)
- Lumens: 632 (12 hr)
- Illuminance: 44 lux @ 5 m (18 hr)
- Lumens: 414 (18 hr)

CONSTRUCTION / PHYSICAL

- Dimensions: 5.82 in dia. (148 mm dia)
- Weight: 0.07 lb (0.031kg)

CERTIFICATIONS / QUALIFICATIONS

- CE
- IP Rating: IP65, temporary outdoor/wet use

WHAT'S INCLUDED

- WELL POD 3 60x10° Filter X 4

