Certificate of Constancy of Performance

0359-CPR-00237



In compliance with Regulation 305/2011/EU of the European Parliament and of the Council of 9 March 2011 (the Construction Products Regulation), this certificate applies to the construction product(s).

Product(s):	JBL Professional Range of High Power 2-Way All Weather Loudspeaker Loudspeakers (refer to attached appendix for details and conditions)	
Produced by or for:	JBL Professional 8500 Balboa Boulevard, Northridge, California, 91329, United State of America	
Produced in the manufacturing plant(s):	Harman de Mexico S. de R.L. de C.V Sor Juana Inés de la Cruz # 20043, Cuidad Industrial, 22444, Tijuana, Mexico	
Intended use:	Fire Safety	
	This certificate attests that all provisions concerning the assessment and verification of constancy of performance described in Annex ZA of the standard(s):	

EN54-24:2008

Fire detection and fire alarm systems. Components of Voice Alarm Systems - Loudspeakers

Under system 1 are applied and that the product(s) fulfils all the prescribed requirements set out above.

This certificate was first issued on **21 October 2013** and will remain valid as long as the test methods and/or factory production control requirements included in the harmonised standard, used to assess the performance of the declared characteristics, do not change, and the product, and the manufacturing conditions in the plant are not modified significantly.

Notified Body 0359

Intertek Testing & Certification Limited Cleeve Road, Leatherhead Surrey, KT22 7SB Tel: + 44 (0)1372 370900 Fax: +44 (0)1372 370977 E-mail: cpd.uk@intertek.com

www.intertek.com

Gordon Ash Certification Manager

Date 21 October 2013

1

Issue

Registered No 3272281 Academy Place, 1-9 Brook Street, Brentwood, Essex, CM14 5NQ, United Kingdom

This Certificate is for the exclusive use of Intertek's client and is provided pursuant to the agreement between Intertek and its Client. Intertek's responsibility and liability are limited to the terms and conditions of the agreement. Intertek assumes no liability to any party, other than to the Client in accordance with the agreement, for any loss, expense or damage occasioned by the use of this Certificate. Only the Client is authorized to permit copying or distribution of this Certificate and then only in its entirety. Any use of the Intertek name or one of its marks for the sale or advertisement of the tested material, product or service must first be approved in writing by Intertek.

Certificate of Constancy of Performance 0359-CPR-00237



Appendix to Certificate of Constancy of Performance 0359-CPR-00237

The details and condition of use for the JBL Professional Range of High Power 2-Way All Weather Loudspeaker Loudspeakers, placed on the market by:

JBL Professional

8500 Balboa Boulevard, Northridge, California, 91329, United State of America

To be used in accordance with the supplier's installation instructions and in conjunction with the following bases, ancillaries, sounder tones and sensitivity settings (*where applicable*):

Products compliant with EN54-24:2008

Variant	Description
AW266-LS	High Power 2-Way All Weather Loudspeaker with 1 x 12" LF (Grey)
AW266-LS-BK	High Power 2-Way All Weather Loudspeaker with 1 x 12" LF (Black)
AW295-LS	High Power 2-Way All Weather Loudspeaker with 1 x 12" LF & Rotatable Horn (Grey)
AW295-LS-BK	High Power 2-Way All Weather Loudspeaker with 1 x 12" LF & Rotatable Horn (Black)
AW526-LS	High Power 2-Way All Weather Loudspeaker with 1 x 15" LF (Grey)
AW526-LS-BK	High Power 2-Way All Weather Loudspeaker with 1 x 15" LF (Black)
AW566-LS	High Power 2-Way All Weather Loudspeaker with 1 x 15" LF & Rotatable Horn (Grey)
AW566-LS-BK	High Power 2-Way All Weather Loudspeaker with 1 x 15" LF & Rotatable Horn (Black)
AW595-LS	High Power 2-Way All Weather Loudspeaker with 1 x 15" LF & Rotatable Horn (Grey)
AW595-LS-BK	High Power 2-Way All Weather Loudspeaker with 1 x 15" LF & Rotatable Horn (Black)

Conditions of use;

Suitable for indoor and outdoor applications

General Notes:

- 1. Tested under Intertek project number 101081608.
- 2. <u>No CE or other type approval is made or inferred outside of the attestation of conformity and the product performance as stipulated on this certificate.</u>

Intertek Testing & Certification Limited, Cleeve Road, Leatherhead, Surrey, KT22 7SB Tel: + 44 (0)1372 370900, Fax: +44 (0)1372 370977, E-mail: cpd.uk@intertek.com

0359-CPR-00237 Issue 1

www.intertek.com

Registered No 3272281 Academy Place, 1-9 Brook Street, Brentwood, Essex, CM14 5NQ, United Kingdom

This Certificate is for the exclusive use of Intertek's client and is provided pursuant to the agreement between Intertek and its Client. Intertek's responsibility and liability are limited to the terms and conditions of the agreement. Intertek assumes no liability to any party, other than to the Client in accordance with the agreement, for any loss, expense or damage occasioned by the use of this Certificate. Only the Client is authorized to permit copying or distribution of this Certificate and then only in its entirety. Any use of the Intertek name or one of its marks for the sale or advertisement of the tested material, product or service must first be approved in writing by Intertek.

Certificate of Constancy of Performance 0359-CPR-00237



Appendix to Certificate of Constancy of Performance 0359-CPR-00237 (continued)

Table of performance for EN54-24:2008 Harmonised technical specification					
Essential characteristics	Performance	Clauses	Notes		
Performance under fire condition.	Pass	4.2, 5.2, 5.3, 5.4, 5.5	а		
Operational Reliability	Pass	4.3, 4.4, 4.5, 5.6, 5.18	b		
Durability of operational reliability: temperature resistance	Pass	5.7, 5.8, 5.9	b		
Durability of operational reliability: humidity resistance	Pass	5.10, 5.11, 5.12			
Durability of operational reliability: corrosion resistance	Pass	5.13			
Durability of operational reliability: impact and vibration resistance	Pass	5.14, 5.15, 5.16, 5.17			
Notes:					

a. The products covered by this standard are assumed to enter the alarm condition, in an event of fire, before the fire becomes so large as to affect their functioning. There is therefore no requirement to function when exposed to direct attack from fire.

b. 5.7, 5.8, 5.9, and 5.18 Type B conditions are applied

Intertek Testing & Certification Limited, Cleeve Road, Leatherhead, Surrey, KT22 7SB Tel: + 44 (0)1372 370900, Fax: +44 (0)1372 370977, E-mail: cpd.uk@intertek.com

0359-CPR-00237 Issue 1

www.intertek.com

Registered No 3272281 Academy Place, 1-9 Brook Street, Brentwood, Essex, CM14 5NQ, United Kingdom

This Certificate is for the exclusive use of Intertek's client and is provided pursuant to the agreement between Intertek and its Client. Intertek's responsibility and liability are limited to the terms and conditions of the agreement. Intertek assumes no liability to any party, other than to the Client in accordance with the agreement, for any loss, expense or damage occasioned by the use of this Certificate. Only the Client is authorized to permit copying or distribution of this Certificate and then only in its entirety. Any use of the Intertek name or one of its marks for the sale or advertisement of the tested material, product or service must first be approved in writing by Intertek.