



CX-500F

Order No.: 0236190

PRODUCTINFOS

Miniature electret instrument microphone,

for sound pickup of flutes.

- Gold-plated back electret cartridge with omnidirectional polar pattern
- Very precise frequency response
- Innovative, glueless fastening system (for tube diameter: 18-26 mm)
- Flexible miniature gooseneck for exact positioning of the microphone
- 4-pole mini XLR inline jack for connection to a pocket transmitter of the IN/PT/UF series, other connection cables are available at option
- Supplied with phantom power supply adapter MA-500 for wired connection to a mixer
- Supplied with robust transport case, phantom power supply adapter and windshield

TECHNICAL SPECIFICATIONS

CX-500F

Description instrument microphone

Transmission method cable



CX-500F

Power supply

Polar pattern omnidir.

System back electret

Audio frequency range 20-20,000 Hz

Nominal impedance 1.5 $k\Omega$

Sensitivity 12.6 mV/Pa

Max. sound pressure 130 dB

DC 48 V, phantom power via power supply

adapter

Housing material plastic Admiss. ambient temp. $0-40~^{\circ}\mathrm{C}$ Weight $8~\mathrm{g}$

Cable 1.4 m

Connection 4-pole mini XLR adapter: XLR, bal.

Packing dimensions (W x H x L) $0.17 \times 0.085 \times 0.37 \text{ m}$

Gross weight 0.752 kg
Net weight 0.52 kg