



KA-10/1PACK

Order No.: 0253120

PRODUCTINFOS

Wireless 16-channel PLL audio transmission system for cameras

- Consisting of a portable audio transmitter and receiver
- Carrier frequency range: 863-865 MHz
- Transmitter and receiver with rechargeable lithium-ion batteries for reducing the weight and to ensure long operating times
- Transmitter can also be used for transmitting line signals (adjustment via recessed gain control)
- Receiver with 3-step PAD switch (0dB/-10 dB/-20 dB) for perfect level matching to the audio input of the camera
- Transmitter and receiver are fitted with a robust metal fixing clip
- Operating time: approx. 12 hours
- Supplied with lavalier microphone in skin design with windshield and tie clip, attachment clip for camera mounting, trim key, dual charging slot with plug-in switch-mode power supply, connection cable with 3.5 mm plug to 3.5 mm plug, connection cable with 3.5 mm plug to XLR plug

Licence-free in the EU.

Supplied w/o camera.

TECHNICAL SPECIFICATIONS

KA-10/1PACK

General information

Description	16-channel PLL audio transmission system
Carrier frequency range	863-865 MHz
Audio frequency range	40-18,000 Hz
Channels	16
THD	< 1%
Admiss. ambient temp.	0-40 °C

Specifications transmitter

Transmitting power	< 10 mW
Operating range	approx. 60 m
Power supply transmitter	3.7 V rech. lithium-ion battery
Width transmitter	55 mm
Height transmitter	100 mm
Depth transmitter	18 mm
Weight transmitter	80 g

Specifications receiver

Audio signal receiver	300 mV/7 kΩ (jack)
Power supply receiver	3.7 V rech. lithium-ion battery
Width receiver	55 mm
Height receiver	100 mm
Depth receiver	18 mm
Weight receiver	82 g
Connections receiver	1 x 3.5 mm jack (transmitter) 1 x 3.5 mm jack (receiver)