



42589

Showtec Compact Par 18 Q4



18x 7 W RGBW LED Par - black

EAN: 8717748478078



The Showtec Compact Par 18 Q4 is a compact 18x 7 watt RGBW LED Par with double bracket for easy floor positioning, suitable for indoor venues. It has a 15° fixed beam angle and features 0 - 100 % dimmer and 20 Hz strobe effects, perfectly suitable for short-throw colour mixing. The Compact Par 18 Q4 can be controlled manually, via DMX and Master/Slave in either Manual, Auto run and Sound-controlled mode with built-in programs. Its design fits in every setting with either black and white housing. A dedicated filter frame holder, filter frame, and power cable are included.

Special features:

- Compact 18x 7 W RGBW LED Par
- Double bracket for easy floor positioning
- Narrow 15° fixed beam angle
- Dimmer and strobe function
- Manual, DMX and Master/Slave control
- Auto run and Sound-controlled mode
- Available in black or white housing

Specifications:

Source

Light Source Type	LED
Light Source Quantity	18
Light Source Power	7 W
LED Colour Type	RGBW
Refresh Rate	12000 Hz
Illuminance @ 2 m	10000 lx
Luminous Flux (Total)	4997 lm

Optical

Beam Angle (Circular)	15°
-----------------------	-----

Control and Programming

Control Mode	Auto / DMX / Manual
DMX Channels	4 / 6 / 10
Protocols	DMX / RDM
Display	LCD

Dynamic Effects

Dimmer	0-100 %
Strobe	0-20 Hz

Electrical Specifications and Connections

Power Supply	100-240 V AC 50/60 Hz
Power Consumption	132 W
Power Connector In	Power Pro Blue
Power Connector Out	Power Pro Grey
DMX Connector	XLR 3P In/Out / XLR 5P In/Out
DMX Connector In	XLR 3P / XLR 5P
DMX Connector Out	XLR 3P / XLR 5P
Cable Length	1.5 m

Mechanical Specifications

Length (mm)	300 mm
Width (mm)	131 mm
Height (mm)	313 mm
Weight	5.2 kg
IP Rating	IP20 (indoor use only)
Housing	Aluminium die-cast
Colour	Black

Product Properties

Cooling	Convection
---------	------------

Rigging

Mounting Options	Clamp / Surface
Safety Attachment	Yes

Thermal Specifications

Maximum Ambient Temperature	40°C
Minimum Operating Temperature	-10°C

Included Items

Included Cables	powerCON cable
Included Accessories	Filter frame holder
Included Rigging	Bracket