

43333

**Showtec Edison Vintage 2 Pale
Gold / Wood Grain**



*Retro DMX LED light with dimmer
and E27 socket - wood grain
pattern*

EAN: 8717748626233



The Showtec Edison Vintage 2 is a large-format vintage-style luminaire. Combining a new design with the same trusted functionality as the Edison Vintage 1, it brings the charm of vintage lighting into the modern era. With an E27 socket, it delivers a cosy glow and elegant retro-inspired look, making it a perfect addition to stages, studios, themed venues and decorative installations. The built-in dimmer supports both DMX control and manual operation, with smooth, non-linear voltage-based dimming for authentic incandescent-style fades. An intuitive OLED display ensures easy configuration, while the quick-lock bracket allows for fast, secure mounting on truss or 50 mm pipe systems.

LED bulb not included.

Special features:

- DMX LED dimmer with E27 socket
- Manual and DMX control
- Quick-lock mounting bracket included
- OLED display for easy control

Specifications:

Source

Light Socket	E27
Number of Sockets	1

Control and Programming

Control Mode	DMX / Manual
DMX Channels	1 / 2
Protocols	DMX / RDM
Display	OLED
Display Size	1.3"
Dim Curve	Linear / Square / I-Square / S-Curve
Dimmer Resolution	16 bit

Dynamic Effects

Dimmer	0-100 %
--------	---------

Electrical Specifications and Connections

Power Supply	100-240 V AC 50/60 Hz
Power Consumption	6.7 W
Max. power consumption	20 W
Fuse	1 A
Power Connector In	Power Pro Blue
Power Connector Out	Power Pro Grey
DMX Connector	XLR 5P In/Out
DMX Connector In	XLR 5P
DMX Connector Out	XLR 5P
Cable Length	1.5 m

Mechanical Specifications

Height (mm)	541 mm
Width (mm)	526 mm
Depth (mm)	239 mm
Weight	5.3 kg
IP Rating	IP20 (indoor use only)
Material	Aluminium / Metal
Housing	Aluminium / Metal
Colour	Pale Gold / Wood Grain

Product Properties

Cooling	Convection
---------	------------

Rigging

Mounting Options	Clamp / Quick-Lock
------------------	--------------------

Thermal Specifications

Maximum Ambient Temperature	45°C
Minimum Operating Temperature	0°C

Included Items

Included Cables
Included Rigging

Power Pro Cable
Quick-Lock Bracket