


33133

Showtec Performer Fresnel 1500 Q6 MKII



200 W RGBALC-colour Theatre & Studio LED Fresnel

EAN: 8717748620682



The Showtec Performer 1500 Fresnel Q6 MKII is a 200-watt RGBALC LED Spot with high CRI and silent operations, suitable for theatrical and studio applications. It projects a bright, soft field of light within a wide 10° - 50° manually adjustable zoom range. The Performer 1500 Fresnel Q6 MKII has a 6-colour LED Engine (RGBALC) with 16 preset colours with a high CRI of 97 for precise colour temperatures. Its 0 - 100 % dimmer function and colour engine are DMX controllable. An optional barndoor enables you to manually shape the output of your Performer 1500 Fresnel Q6 MKII.

Special features:

- 200 W RGBALC LED Fresnel
- Suitable for theatrical and studio applications
- CCT colour temperature range of 1800 K - 10000 K
- Wide manually adjustable zoom range
- 16 preset colours

Specifications:

Source

Light Source Type	LED
Light Source Quantity	1
Light Source Power	200 W
LED Colour Type	RGBALC
Refresh Rate (Max.)	25 kHz
Illuminance @ 5 m	3052 lx
Luminous Flux (Total)	6213 lm
CRI	97
Minimum CCT	1800 K
Maximum CCT	10000 K

Optical

Beam Angle Minimum (Circular)	10°
Beam Angle Maximum (Circular)	50°
Field Angle Minimum (Circular)	18°
Field Angle Maximum (Circular)	75°
Zoom Type	Manual

Control and Programming

Control Mode	DMX / Master Slave / Stand Alone
DMX Channels	3 / 7 / 8 / 10 / 13 / 20
Protocols	DMX / RDM
Display	LCD

Dynamic Effects

Dimmer	0-100 %
--------	---------

Electrical Specifications and Connections

Power Supply	100-240 V AC 50/60 Hz
Power Consumption	170 W
Power Connector In	Power Pro True
Power Connector Out	Power Pro True
DMX Connector	XLR 5P In/Out
DMX Connector In	XLR 5P
DMX Connector Out	XLR 5P

Mechanical Specifications

Length (mm)	450 mm
Width (mm)	290 mm
Height (mm)	370 mm
Weight	5.3 kg
IP Rating	IP20 (indoor use only)
Housing	Aluminium die-cast
Colour	Black

Product Properties

Cooling	Axial fan
---------	-----------

Thermal Specifications

Maximum Ambient Temperature	45°C
Minimum Ambient Temperature	0°C

Included Items

Included Cables	Power Pro True Cable
-----------------	----------------------