



33063

**Showtec Performer Profile 600
DDT**



*250 W Warm White DDT Theatre
LED ellipsoidal*

EAN: 8717748418203



The Showtec Profile 600 DDT is a 250 watt Warm White COB LED ellipsoidal with high CRI and silent operations, suitable for theatrical applications. Its DDT-model (Direct triac Dimming Technology) is compatible with a conventional dimming infrastructure. The Performer Profile 600 features a 3200 K colour temperature and 0 - 100 % DMX controllable dimmer allowing a selection between 4 different curves. Optional industry standard fixed and zoom lenses allow a proper projection of hard-edge, precisely focused light where needed.

Special features:

- 250 W Warm White COB LED ellipsoidal
- Suitable for theatrical and studio applications
- DDT-model compatible with a halogen infrastructure
- High CRI for accurate 3200 K colour rendering
- DMX dimmer function with 4 preset curves
- Silent operation
- Hard edge, precisely focused field of light
- Optional fixed and zoom lenses and gobo holders

Specifications:

Source

Light Source Type	LED
Light Source Quantity	1
Light Source Power	250 W
LED Colour Type	WW
Refresh Rate (Max.)	25 kHz
Luminous Flux (Total)	10000 lm
Maximum CCT	3200 K

Control and Programming

Control Mode	DMX
DMX Channels	1 / 2 / 3
Protocols	DMX
Display	LCD
Dim Curve	Linear / Square
Dimmer Resolution	16 bit

Dynamic Effects

Dimmer	0-100 %
--------	---------

Electrical Specifications and Connections

Power Supply	100-240 V AC 50/60 Hz
Power Consumption	270 W
Power Connector In	powerCON Blue
Power Connector Out	powerCON Grey
DMX Connector	XLR 3P In/Out / XLR 5P In/Out
DMX Connector In	XLR 3P / XLR 5P
DMX Connector Out	XLR 3P / XLR 5P

Mechanical Specifications

Length (mm)	720 mm
Width (mm)	380 mm
Height (mm)	340 mm
Weight	9.6 kg
IP Rating	IP20 (indoor use only)
Housing	Aluminium die-cast
Colour	Black

Product Properties

Cooling	Convection/Axial fan
---------	----------------------

Thermal Specifications

Maximum Ambient Temperature	80°C
Maximum Surface Temperature	45°C
Minimum Operating Temperature	-10°C

Included Items

Included Cables	powerCON cable
-----------------	----------------