


*Incl. light bulbs & powerCON
cable*

EAN: 8717748290458



The Sunstrip Active MKII is the successor of the already popular Sunstrip Active. It is equal to the Sunstrip Active however this version offers you some extra features such as: invert function, opportunity to change the logo in the display into your company name, protection function for the mode button and fast addressing. The Sunstrip Active MKII has four DMX modes: 1 channel, 2 channel, 5-channel and 10 channel. For stand-alone applications, the Sunstrip Active MKII is equipped with 16 built-in patterns as well as a manual dimmer. With its Neutrik powerCON in- and output the Sunstrip is suitable for the most demanding users on the road. For easy mounting the Sunstrip Active MKII is equipped with two Wall/Floor brackets as well as several M10 nuts, in order to put your clamp in any desired position. For optimal creativity we recommend the special multibracket (30713).

Special features:

- Including 10x Osram bulbs
- Lockable menu
- 10 sections zone control
- Manual chase and DMX mode
- Including floor brackets
- Invert function
- Programmable name in start screen

Specifications:

Source

Light Source Type	Halogen
Light Source Quantity	10
Light Source Power	50 W
Drive Current	3.5 A
Light Socket	GU10
Number of Sockets	10
CRI	95
CCT	3000 K

Control and Programming

Control Mode	Built-in Program / DMX / Manual / Master Slave
DMX Channels	1 / 2 / 5 / 10
Protocols	DMX
Display	7-segment

Dynamic Effects

Dimmer	0-100 %
--------	---------

Electrical Specifications and Connections

Power Supply	240 V AC 50/60 Hz
Power Consumption	550 W
Power Connector In	powerCON Blue
Power Connector Out	powerCON Grey
DMX Connector	XLR 3P In/Out
DMX Connector In	XLR 3P
DMX Connector Out	XLR 3P

Mechanical Specifications

Length (mm)	1000 mm
Width (mm)	130 mm
Height (mm)	160 mm
Weight	6.2 kg
IP Rating	IP20 (indoor use only)
Material	Steel
Housing	Metal / Steel
Colour	Black

Rigging

Mounting Options	Bracket / Clamp / Surface
Safety Attachment	No

Thermal Specifications

Maximum Ambient Temperature	40°C
-----------------------------	------

Included Items

Included Cables	powerCON cable
Included Rigging	Bracket