


With tungsten simulation

EAN: 8717748462695



The Showtec Sunstrip LED is the successor of the already popular Sunstrip Active. The Sunstrip LED has five DMX modes: 1, 2, 3, 10 and 20 channel. Next to DMX it can be controlled in Manual, Auto or Master / Slave Mode. The DMX 3 & 5-pin and powerCON in/output make the Sunstrip LED easy to daisy-chain in every setup. Through the Tungsten mode the Sunstrip LED works like conventional bulbs while there is still an option to operate them in Warm white, Cool white or a combination of both. The Sunstrip LED is equipped with two Wall/Floor brackets in order to put your Sunstrip in any desired position.

Special features:

- 10x 14 W White Sunstrip LED
- 3 selectable dimmer modes: tungsten, warm white and cool white
- Smooth tungsten simulation
- 10 sections zone control
- Manual, DMX and Master/Slave control in manual, auto and sound mode
- Including floor brackets
- Multibracket and dedicated flight case are optional

Specifications:

Source

Light Source Type	LED
Light Source Quantity	10
Light Source Power	14 W
LED Colour Type	WW / CW
Refresh Rate	1525 Hz
Luminous Flux (Total)	2800 lm
CRI	80

Optical

Beam Angle (Horizontal)	20°
Beam Angle (Vertical)	20°

Control and Programming

Control Mode	Auto / DMX / Manual / Master Slave
DMX Channels	1 / 2 / 3 / 10 / 20
Protocols	DMX / RDM
Display	OLED
Dim Curve	Linear / Square / I-Square / S-Curve
Zone Control (Sections)	10

Dynamic Effects

Dimmer	0-100 %
Strobe	0-20 Hz

Electrical Specifications and Connections

Power Supply	100-240 V AC 50/60 Hz
Power Consumption	120 W
Power Connector In	Power Pro Blue
Power Connector Out	Power Pro Grey
DMX Connector	XLR 3P In/Out / XLR 5P In/Out
DMX Connector In	XLR 3P / XLR 5P
DMX Connector Out	XLR 3P / XLR 5P

Mechanical Specifications

Length (mm)	1000 mm
Width (mm)	146 mm
Height (mm)	176 mm
Weight	7 kg
IP Rating	IP20 (indoor use only)
Material	Aluminium / Metal
Housing	Metal
Colour	Black

Product Properties

Cooling	Convection/Axial fan
---------	----------------------

Rigging

Mounting Options	Clamp
------------------	-------

Safety Attachment	Yes
Safety Eyes	2
Thermal Specifications	
Maximum Ambient Temperature	40°C
Maximum Surface Temperature	70°C
Included Items	
Included Cables	powerCON cable
Included Rigging	Bracket